



SÜLLBERG

MAIN PARTICULARS

Built : Barkemeijer Strobos, Nederlands 1994 as general cargo ship
converted into Tanker 2007

Type : Tanker

Classification : GL 100A5 M Product Carrier ESP

Flag : Portugal

Call Sign : CQIE2

GT : 1943

NT : 976

Deadweight : abt. 3.164 mt

Cargo Tanks : abt. 3.459 m³ in 12 Tanks

Length o.a : 89.50 m

Length bpp : 84,99 m

Breadth mld. : 12,50 m

Draught : 4,63 m

Speed : abt. 10 kn

Rules and regulations

- International Convention for the Safety of Life at Sea (SOLAS) 1974, And its Protocol of 1988 , consolidate edition 2001 , amendments 2000 Up to and including 2002 , as far as applicable to this type of Vessel .
- International Convention on Load Lines 1966 with 1988 Protocol and Amendments up to and including 2003 amendent (Entry into force 1-1-2005).
- International Convention for the Prevention of Pollution from Ship , 1973 , As modified by Protocol of , (MARPOL 73/78) , Annex I , consolidated Edition 2002 and amendments coming into force on 1-1-2005.
- OCIMF “ Recommendations for OIL Tanker Manifolds and Associated Equipment (as far as applicable)
- ILO Convention 147 , as far as applicable

Specification

Propelling Machinery	: 1 Deutz MWM
Type	: SBV6M628
Power	: 599 KW
Propeller	: Fixed
Bowtruster	: Veth
Type	: VT 150
Power	: 275 hp
Auxiliary Engines	: 2 x Diesel Generator 112 KVA 1 x Emergency Generator 60 KVA 1 x Power Plan for Cargo Pumps 500 KVA
Equipment	: European Trade . 200 Mils from Coast . Cargo only IFO 380 Product + 200 ts Gasoil

Cargo Pumps : 3 x Vogelsang
Type : VX 186-386 QD
Pumping Capacity : 323 m³ per Hrs
Power using : 71,4 KW per Pump

Rest Pump : 1x Vogelsang
Type : V 100 – 90 Q HD
Pumping Capacity : 10 m³/h
Power using : 1,6 KW
Class : MARPOL. 73/78 with additional equipments 97

Cargo Blender : 1X Sulzer
Type : Sulzer Mischer SMV DN 250
Capacity : 646 m³/h

Cargo Flowmeter : 2 X Mar in Controls
Type : MIC LBM 3000 / MIC LBM 1000
Max. flowrate : 780 m³/ h

Tank Level Measuring : 1X Hoppe
Type : TT 1040194-dd

Tank Temperature Measuring : 1X Meramont

Boiler : HTI Gesab
Type : HE 10 H 40
Power : 1250 KW
Oil : Thermaloil for cargo tank heating

Crane : Bütter
Outreach : 20 MTR max 0.9 TS
Type : SK 10-22
Power : 2 x 4 KW
Nutzlast : 1000 daN

Deck Foam System : Unitor
Type : 530
Monitor : 5

Freefall Boat : Ernst Hatecke
Type : GFF 4,9M (-T)
Davitsystem : FFA 4,9M
Class : GL , SeeBG
System for : 10 Person

All details about- Without Guarantee
For Time Charter Description contact our Chartering Department
Contact: Tel: +49 4086667546 / email: management@vega-reederei.de